

Section 1: IDENTIFICATION

Product Name: #1 ULSD Dyed (Superior)

Synonyms: #1 Ultra Low Sulfur Diesel Dyed, #1 Fuel Oil Dyed, #1 Off Road Diesel.

Product Use: Motor fuel. Heating fuel.

Restrictions on Use: Not available.

Manufacturer/Supplier: Superior Refining Company, LLC (Husky Energy)
2407 Stinson Ave
Superior, WI 54880

Phone Number: 403-298-6111

Emergency Phone: Chemtrec: 1-800-424-9300
877-262-2111

Date of Preparation of SDS: October 14, 2020

Section 2: HAZARD(S) IDENTIFICATION**GHS INFORMATION**

Classification: Flammable Liquids, Category 3
Skin Irritation, Category 2
Specific Target Organ Toxicity (Single Exposure), Category 3 - Narcotic Effects
Aspiration Hazard, Category 1

LABEL ELEMENTS**Hazard****Pictogram(s):****Signal Word:** Danger

Hazard Statements: Flammable liquid and vapor.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical, ventilating, and lighting equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Avoid breathing mist, vapours, or spray.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing and eye protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
 Do NOT induce vomiting.
 If skin irritation occurs: Get medical attention.
 Take off contaminated clothing and wash it before reuse.
 In case of fire: Use dry chemical, CO₂, water spray or regular foam to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed.
 Keep cool.
 Store locked up.

Disposal: Dispose of contents and container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS			
Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.
Kerosine (petroleum)	Kerosene	8008-20-6	100

Section 4: FIRST-AID MEASURES	
Inhalation:	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately. Acute and delayed symptoms and effects: May cause drowsiness or dizziness. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.
Eye Contact:	If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
Skin Contact:	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse.

Acute and delayed symptoms and effects: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: If swallowed: Do NOT induce vomiting. Immediately call a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth to an unconscious person. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately.

Acute and delayed symptoms and effects: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Flammable liquid and vapor. Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

Fire involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static Discharge: Take action to prevent static discharges. This material is sensitive to static discharge.

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical, CO₂, water spray or regular foam.

Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media: Do not use straight streams.

Products of Combustion: Oxides of carbon.

Protection of Firefighters: Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control or dilution water may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide

limited protection.

Section 6: ACCIDENTAL RELEASE MEASURES

- Emergency Procedures:** As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded.
- Personal Precautions:** Do not touch or walk through spilled material. Use personal protection recommended in Section 8.
- Environmental Precautions:** Prevent entry into waterways, sewers, basements or confined areas.
- Methods for Containment:** Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors.
- Methods for Clean-Up:** Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material.
- Other Information:** See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE**Handling:**

Do not swallow. Avoid breathing mist, vapours, or spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines****Component**

Kerosene [CAS No. 8008-20-6]

ACGIH: 200 mg/m³ (TWA); Skin; A3; Application restricted to conditions in which there are negligible aerosol exposures (2003)

OSHA: No PEL established.

PEL: Permissible Exposure Limit

TWA: Time-Weighted Average

- Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits. Use explosion-proof electrical, ventilating, and lighting equipment.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

- Eye/Face Protection:** Wear chemical safety goggles. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.
- Hand Protection:** Wear protective gloves. Consult glove manufacturer specifications for further information.
- Skin and Body Protection:** Wear protective clothing. Flame resistant clothing that meets the NFPA 2112 and CAN/CGSB 155.20 standards is recommended in areas where material is stored or handled.
- Respiratory Protection:** If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4, with organic vapor cartridge, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.
- General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear, coloured liquid.
Colour:	Various.
Odour:	Characteristic. Hydrocarbon.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	Not available.
Melting Point / Freezing Point:	-50.2 °C (-58.4 °F)
Initial Boiling Point:	68.9 °C (156 °F)
Boiling Range:	68.9 to 124.4 °C (156 to 256 °F)
Flash Point:	45.5 °C (114 °F) (Closed Cup)
Evaporation Rate:	Not available.
Flammability (solid, gas):	Not applicable.
Lower Flammability Limit:	Not available.

Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density:	0.783 (Water = 1)
Solubilities:	Insoluble in the following materials: cold water and hot water.
Partition Coefficient: n-Octanol/Water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	1.19 cSt at 40 °C (104 °F)
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.
Density:	Not available.
Coefficient of Water/Oil Distribution:	Not available.

Section 10: STABILITY AND REACTIVITY

Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Chemical Stability:	Stable under normal storage conditions.
Possibility of Hazardous Reactions:	None known.
Conditions to Avoid:	Contact with incompatible materials. Sources of ignition. Exposure to heat.
Incompatible Materials:	Strong oxidizers.
Hazardous Decomposition Products:	Not available.

Section 11: TOXICOLOGICAL INFORMATION
--

EFFECTS OF ACUTE EXPOSURE
Product Toxicity

Oral:	Not available.
Dermal:	Not available.
Inhalation:	Not available.

Component Toxicity

Component	CAS No.	LD₅₀ oral	LD₅₀ dermal	LC₅₀
Kerosene	8008-20-6	> 2835 mg/kg (rabbit)	> 2000 mg/kg (rabbit)	> 5000 mg/m ³ (rat); 4H

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Central nervous system.

Symptoms (including delayed and immediate effects)

Inhalation: May cause drowsiness or dizziness. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.

Eye: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization: Not available.

Respiratory Sensitization: Not available.

Medical Conditions Aggravated By Exposure: Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Cardiovascular system. Central nervous system.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation. High vapour concentrations, generally greater than 10% by volume, may sensitize the heart and lead to lethal cardiac arrhythmias.

Carcinogenicity: Product is not classified as a carcinogen. See Component Carcinogenicity table below for information on individual components. Straight run Kerosene has shown the potential to cause skin cancer in laboratory animals when applied over the life time of the animal.

Component Carcinogenicity

Component	ACGIH	IARC	NTP	OSHA	Prop 65
Kerosene	A3	Not listed.	Not listed.	Not listed.	Not listed.

Mutagenicity: Not available.

Reproductive Effects: Not available.

Developmental Effects

Teratogenicity: Not available.

Embryotoxicity: Not available.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Other Adverse Effects: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions: Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

Section 14: TRANSPORT INFORMATION**U.S. Department of Transportation (DOT)**

Proper Shipping Name: NA1993, DIESEL FUEL, 3, PG III

Class: 3

UN Number: NA1993

Packing Group: III

Label Code:

**Canada Transportation of Dangerous Goods (TDG)**

Proper Shipping Name: UN1223, KEROSENE, 3, PG III

Class: 3

UN Number: UN1223

Packing Group: III

Label Code:

**Section 15: REGULATORY INFORMATION****Chemical Inventories****US (TSCA)**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations**United States**

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

No components are listed.

State Regulations**Massachusetts**

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Component	CAS No.	RTK List
Kerosene	8008-20-6	Listed.

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

Component	CAS No.	RTK List
Kerosene	8008-20-6	Listed.

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component	CAS No.	RTK List
Kerosene	8008-20-6	Listed.

California**California Prop 65:** This product does not contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.**Section 16: OTHER INFORMATION****Disclaimer:**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS: October 14, 2020**Version:** 2.0**GHS SDS Prepared by:** Deerfoot Consulting Inc.**Phone: (403) 720-3700**